

TCX45 Tire Changer

Easy-to-use conventional tire changer



Specifications

Electrical

-1-1-6	110V, 1ph, 60Hz
-2-1-6	220V, 1ph, 60Hz
-2-1-5	220V, 1ph, 50Hz

Wheel clamping

External (min-max)	11 - 22 in.
Internal (min-max)	13 - 25 in.

Maximum tire diameter	980 mm
------------------------------	--------

Maximum rim width	12 in.
--------------------------	--------

Bead loosener width	320 mm
----------------------------	--------

Table rotation speed	8.5 rpm
-----------------------------	---------

Noise level	70 dB
--------------------	-------

Operation pressure	8 - 10 bar
---------------------------	------------

Machine weight	208 kg
-----------------------	--------

Dimensions

Height	1940 mm
Width	1115 mm
Depth	960 mm

Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.

Models

TCX45 Swing arm tire changer

TCX45GP Swing arm tire changer with tubeless inflation

Add:

-1-1-6 For 110V, 1ph, 60Hz

-2-1-6 For 220V, 1ph, 60Hz

-2-1-5 For 220V, 1ph, 50Hz

Standard equipment

- ✓ Inflation hose and gauge
- ✓ Tire lever
- ✓ Spare mount head protectors
- ✓ Double-acting shovel cylinder

Optional equipment

RP11-8-11120032 Bead press arm upgrade

RP11-8-11100044 Plastic jaw protectors


RP11-801258383 Side shovel protectors (6)

RP11-8-11400098 Bead lever protectors (4)



TCX45GP with optional bead press arm

TCX45



Be sure to check out other Hunter literature for more quality products from Hunter Engineering.

HUNTER
Engineering Company

www.hunter.com

11250 Hunter Drive, Bridgeton, MO 63044, USA
Tel: 1-314-731-3020, Fax: 1-314-731-0132
Email: international@hunter.com

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

0917BH

Copyright © 2017, Hunter Engineering Company

Form 7084-TE-05, 09/17
Supersedes form 7084-TE-05, 12/15