

# ***TCX45 Tire Changer***

***Easy-to-use conventional tire changer***



# Specifications

## Electrical

-1-1-6	110V, 1ph, 60Hz
-2-1-6	220V, 1ph, 60Hz
-2-1-5	220V, 1ph, 50Hz

## Wheel clamping

External (min-max)	11 - 22 in.
Internal (min-max)	13 - 25 in.

<b>Maximum tire diameter</b>	980 mm
------------------------------	--------

<b>Maximum rim width</b>	12 in.
--------------------------	--------

<b>Bead loosener width</b>	320 mm
----------------------------	--------

<b>Table rotation speed</b>	8.5 rpm
-----------------------------	---------

<b>Noise level</b>	70 dB
--------------------	-------

<b>Operation pressure</b>	8 - 10 bar
---------------------------	------------

<b>Machine weight</b>	208 kg
-----------------------	--------

## Dimensions

Height	1940 mm
Width	1115 mm
Depth	960 mm

Some dimensions, capacities and specifications may vary depending on tire and wheel configurations.

## Models

**TCX45** Swing arm tire changer

**TCX45GP** Swing arm tire changer with tubeless inflation

Add:

**-1-1-6** For 110V, 1ph, 60Hz

**-2-1-6** For 220V, 1ph, 60Hz

**-2-1-5** For 220V, 1ph, 50Hz

## Standard equipment

- ✓ Inflation hose and gauge
- ✓ Tire lever
- ✓ Spare mount head protectors
- ✓ Double-acting shovel cylinder

## Optional equipment

**RP11-8-11120032** Bead press arm upgrade

**RP11-8-11100044** Plastic jaw protectors

**RP11-801258383** Side shovel protectors (6)

**RP11-8-11400098** Bead lever protectors (4)



**TCX45GP** with optional bead press arm

**TCX45**



Be sure to check out other Hunter literature for more quality products from Hunter Engineering.

**HUNTER**  
Engineering Company

[www.hunter.com](http://www.hunter.com)

11250 Hunter Drive, Bridgeton, MO 63044, USA  
Tel: 1-314-731-3020, Fax: 1-314-731-0132  
Email: [international@hunter.com](mailto:international@hunter.com)

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

0917BH

Copyright © 2017, Hunter Engineering Company

Form 7084-TE-05, 09/17  
Supersedes form 7084-TE-05, 12/15