


WINALIGN® LITE

HS223 Series Sensors

HUNTER
Engineering Company

SPECIFICATIONS / FEATURES / MEASUREMENTS []



| HS223: | CM | ML | FC | WM |
|--|--|---|---------------------------------|----------------------|
| Sensor Mount Type | Manually Adjustable Mobile Cabinet Mount | Manually Adjustable Single Column Floor Mount | Fixed Single Column Floor Mount | Wall / Ceiling Mount |
| Power Requirements | Supplied by Console | | | |
| HQ Targets w/Quick Grip Adaptors | ✓ | ✓ | ✓ | ✓ |
| Vertical Camera Adjustment | ✓ | ✓ | | |
| Mobile - Bay-to-Bay | ✓ | | | |
| High Resolution Cameras | ✓ | ✓ | ✓ | ✓ |
| Multiple Target Storage Configurations | ✓ | ✓ | ✓ | ✓ |

Front



Rear



SPECIFICATIONS

| | |
|------------------------------------|---------------------------------|
| Weight of Front Target | 3.2 kg (7 lbs) |
| Profile of Front Target | 457 mm (18 in) |
| Weight of Rear Target | 3.4 kg (7.5 lbs) |
| Profile of Rear Target | 482 mm (19 in) |
| Installation Time | 5 seconds |
| Rolling Compensation Style | Forward |
| Camera Resolution | 2,608 x 1,952 10,000,000 px |
| Track Width | 2032 mm (80 in.) |
| Wheel Base | 5334 mm (210 in.) |
| Distance to Wall | 1651 - 2464 mm (66 - 97 in.) |
| Suggested Distance | 2464 mm (97 in.) |
| Short Bay Distance (see site info) | 1651 mm (65 in.) |

MEASUREMENTS

| | |
|-------------------------|---|
| S.A.I. & Included Angle | ✓ |
| Set Back | ✓ |
| Max Steering Angle | ✓ |
| Wheelbase Difference | ✓ |
| Track Width Difference | ✓ |
| Tread Width Difference | ✓ |
| Lateral Offset | ✓ |
| Rear Set Back | ✓ |
| Axle Offset | ✓ |

For alignment information visit:
hunter.com/alignment-machines

For local contact visit:
hunter.com/contact

For general inquiries visit:
www.hunter.com or call 800-448-6848

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

Form AS08243-05, 11-24
Copyright ©2024, Hunter Engineering Company

WINALIGN® LITE

HS223 Series Sensors


HUNTER
Engineering Company

DIMENSIONS / WEIGHTS []


| HS223: | CM | ML | FC | WM |
|--------------------------------|-------------------------------|--------------------------------|--------------------|---------------------------|
| Width (W) | 2667 mm (105 in) | 2667 mm (105 in) | 2667 mm (105 in) | 2667 mm (105 in) |
| Height (H) | 2997 mm (118 in) | 3112 mm (122.5 in) | 3112 mm (122.5 in) | 762 mm (30 in) |
| Depth (D) | 635 mm (25 in) | 381 mm (15 in) | 381 mm (15 in) | 381 - 762 mm (15 - 30 in) |
| Vertical Camera Movement Range | 1524 - 2426 mm (60 - 95.5 in) | 1422 - 2883 mm (56 - 113.5 in) | N/A | N/A |

* Use of Wall Mount Extension Kit adds additional 686 - 1143 mm (27 - 45 in) to depth.

Vertically Adjustable Manual Lift Camera Sensors



Fixed Position Camera Sensor



Included with all HS223 Sensors



For more details on site requirements refer to form AF08247-00.