BENCH LATHES

BL Series Brake Lathes

SPECIFICATIONS []






BL73 shown with optional bench, hood & tablet. * with 1-7/8" Arbor. **19.5" with hood

	BL1x BL7x (with ACT / Digi-Cal)		
Power Requirements			
Domestic	115 V, 15 A, 50-60 Hz, 1ph	115 V, 15 A, 50-60 Hz, 1ph	
Optional	220 V, 7.5 A, 50-60 Hz, 1ph	220 V, 7.5 A, 50-60 Hz, 1ph	
International	220 V, 7.5 A, 50-60 Hz, 1ph	220 V, 7.5 A, 50-60 Hz, 1ph	
Optional	115 V, 15 A, 50-60 Hz, 1ph	NA	
	Base Model	With Anti-Chatter Technology	
Rotor Diameter**	6-22 in. (152.4 - 584.2 mm)	6-22 in. (152.4 - 584.2 mm)	
Rotor Max Width	5 3/8 in. (136.5 mm)	5 3/8 in. (136.5 mm)	
Rotor Max Thickness	2 in. (50.8 mm)	2 in. (50.8 mm)	
Drum Diameter**	6 - 24 in. (152.4 - 609.6 mm)	6 - 24 in. (152.4 - 609.6 mm)	
Drum Max Width	8 in. (203.2 mm)	8 in. (203.2 mm)	
Max Arbor Weight*	200 lbs (90.7 kg)*	200 lbs (90.7 kg)*	
Motor	1.5 hp (1.12 kw)	1.5 hp (1.12 kw)	
Spindle Speeds	85 / 110 / 175 rpm	85 / 110 / 175 rpm	
Feed Rate	002014 in. / rev (.0536 mm/rev.) Infinitely Variable	002014 in. / rev (.0536 mm/rev.) Infinitely Variable	

			-		-	
BL-	10	11	13	70	71	73
Tablet				 ✓ 	 ✓ 	
Rotor Capability	~	~	~	~	 	~
ACT / DigiCal 2.0				~	 ✓ 	~
Bench		~	~		 	~
Dust Collection Hood			~			~
Width (W)	48 in. (1219 mm)	43.5 in. (1105 mm)	45 in. (1143 mm)	43.5 in. (1105 mm)	45 in. (1143 mm)	48 in. (1219 mm)
Height (H)	13 in. (330 mm)	75.5 in. (1918 mm)	75.5 in. (1918 mm)	13 in. (330 mm)	75.5 in. (1918 mm)	75.5 in. (1918 mm)
Depth (D)	36.5 (927 mm)	41 in. (1041 mm)	53.5 in. (1359 mm)	36.5 (927 mm)	41 in. (1041 mm)	53.5 in. (1359 mm)







For balancer information visit: hunter.com/brake-lathes

For local contact visit: hunter.com/contact For general inquiries visit: www.hunter.com or call 800-448-6848

Because of continuing technological advancements, specifications, models and options are subject to change without notice.

Form LS07698-00, 06-24 Supersedes Form LS07698-00, 06-23 Copyright ©2024, Hunter Engineering Company